

Part Code	R1600_L
Lid Code	R1600_L_L
Tub Code	R1600_L_T
Handle Code	-

Technical Data Sheet


PART NO. R1600_L




FRONT VIEW



SIDE VIEW



TOP VIEW



ISOMETRIC VIEW

KEY DIMENSIONS

LENGTH
241.9 mm

WIDTH
167.3 mm

HEIGHT
65.8 mm

BRIMFUL
1980.0 ml

DIMENSION	**WEIGHT**
Length (side view) **241.9 mm (± 2%)** Width (front view) **167.3 mm (± 2%)** Height (front view) **65.8 mm (± 2%)** Brimful volume **1980.0 ml**	Weight tub: **66.0 g** Weight lid: **32.0 g** Total weight: **98.0 g**

DECORATION	**IML ✓**		
RAW MATERIAL	**Raw material options: Polypropylene (PP)**		
PACKAGING	**Carton dimensions: 62 x 48 x 45 cm (L x W x H)**		
	20' ft container	**40' HC container**	**Truck (650 box)**

PERFORMANCE	
HOT FILLING	Material selected for hot filling has very good heat resistance and is suitable for hot filling. Packaging becomes flexible under hot-fill temperatures; take care when stacking immediately after filling. Allow the product to cool and reach its original stacking strength before palletizing.
IN COLD WEATHER	The standard raw material for white and transparent products resists temperatures down to -20°C. Deep freezing below -20°C may require a special raw material available on request.
SHELF LIFE	Compliance of the products to the technical specifications in this data sheet is guaranteed for 12 months after the date of delivery. Products should be kept in suitable dry storage, away from direct sunlight, and should not exceed the viability of stacking over a long period.
QUALITY INFORMATION	Certified to: ISO 9001:2015, ISO 45001:2018, ISO 22000:2018, ISO 14001:2015. Certificate documents to be inserted here once provided.